

### **TECHNICAL DATA SHEET**

## LED Track Light / EN-TLF020-02, EN-TLF030-02

VERSION - 31.08.2017

## **STANDARD LUMINAIRE**

Reference EN-TLF020-01 EN-TLF030-01 Power 20 W 30 W Current 500 mA 700 mA **Protection Class** IP20 IP20

Dimensions 3-pin track: ø76 x Ht.231.97mm

4-pin track: ø76 x Ht.252.57mm

Voltage AC220-240V, 50-60Hz Led Type Cree Cob Led CRI 80+ OR 90+ Beam Angle 25°, 38°

No Track or Surface-Mounted Installation

-20°C ~ +45°C Working T° Warranty 5 years

**FINISH** 

Dimmable

Standard White, Black, Silver

### **ON REQUEST**

CRI 80+, 90+ Beam Angle 24° or 38° Installation Type On 3-pin track On 4-pin track

Surface-Mounted

# **COLOR TEMPERATURE & LUMINOUS FLUX**

EN-TLF020-01

2'700K 3'000K 4'000K 5'000K 1600 lm ±5% 1760 lm ±5% 1800 lm ±5% 1900 lm ±5%

EN-TLF030-01

3'000K 4'000K 5'000K 2'700K 2400 lm ±5% 2640 lm ±5% 2700 lm ±5% 2850 lm ±5%

# **CERTIFICAT**

Œ

## **MAIN FEATURES:**

- Sleek cylindrical shape in foldable design with real 2 in 1 flexible
- Beam angle can be change easily by remplacing lens without any tool.
- Track head rotates through 355° and pivots through 90°

### **APPLICATION:**

- Optimum accent lighting for museums, exhibitions, art galleries, sales and showroom areas.



# **TECHNICAL DRAWINGS** 3-pin track 4-pin track 90.6 68. 231.97 184.4<del>7</del> 252. 184.47 **Ø**76 **Ø**76









