

TECHNICAL DATA SHEET

LED Track Light, Adjustable Beam Angle / EN-TLI015-01, EN-TLI015-02

VERSION - 01.09.2017

STANDARD LUMINAIRE

Reference EN-TLI015-01 (Adjustable beam angle)

EN-TLI015-02 (Adjustable beam angle + buit-in dimmer)

 Power
 15 W

 Current
 350 mA

 Protection Class
 IP20

Dimensions 3-pin track: ø75 x Ht.255.5mm

4-pin track: ø76 x Ht.266.5mm

Voltage AC220-240V, 50-60Hz

Beam Angle Adjustable : 15° to 90° or 15° to 70°

Dimmable Yes

Installation Track, Pendant or Surface-Mounted

Working T° $-20^{\circ}\text{C} \sim +45^{\circ}\text{C}$ Warranty 5 years

FINISH

Standard White, Black, Silver

ON REQUEST

CRI **80+, 90+**

Beam Angle Adjustable : 15° to 90°

Adjustable: 15° to 70°

Installation Type On 3-pin track

On 4-pin track Pendant

Surface-Mounted

Dimming Option Triac, 1-10V

Ask technical departement for more information

COLOR TEMPERATURE & LUMINOUS FLUX

EN-TLI015-01 + EN-TLI015-02

 2'700K
 3'000K
 4'000K
 5'000K

 1035 lm ±5%
 1170 lm ±5%
 1215 lm ±5%
 1245 lm ±5%

CERTIFICAT

 ϵ

MAIN FEATURES:

- Sleek design with buit-in driver
- By adjusting the focal length, the beam angle can be changed from 15° to 90° or 15° to 70° $\,$
- Track head rotates through 355° and pivots through 90°

APPLICATION:

- Optimum accent lighting for museums, exhibitions, art galleries, sales and showroom areas.















