

#### **TECHNICAL DATA SHEET**

## LED Track Light, Adjustable Beam Angle / EN-TLI020-01, EN-TLI020-01

VERSION - 01.09.2017

#### **STANDARD LUMINAIRE**

Reference EN-TLI020-01 (Adjustable beam angle)

EN-TLI020-02 (Adjustable beam angle + buit-in dimmer)

Power 20 W Current 500 mA **Protection Class** IP20

Dimensions 3-pin track: ø75 x 176.5 x Ht.217.9mm

4-pin track: ø76 x 215.1 x Ht.228mm

Voltage AC220-240V, 50-60Hz Led Type Cree Cob Led

CRI 80+ OR 90+

Beam Angle Adjustable: 15° to 90° or 15° to 70°

Dimmable Yes

Installation Track, Pendant or Surface-Mounted

Working T° -20°C ~ +45°C Warranty 5 years

**FINISH** 

Standard White, Black, Silver

**ON REQUEST** 

CRI 80+, 90+

Beam Angle Adjustable: 15° to 90°

Adjustable: 15° to 70°

Installation Type On 3-pin track

On 4-pin track Surface-Mounted

**Dimming Option** Triac, 1-10V

Ask technical departement for more information

#### **COLOR TEMPERATURE & LUMINOUS FLUX**

EN-TLI015-01 + EN-TLI015-01

2'700K 3'000K 4'000K 5'000K 1340 lm ±5% 1460 lm ±5% 1540 lm ±5% 1600 lm ±5%

# **CERTIFICAT**

Œ

## **MAIN FEATURES:**

- Sleek design with buit-in driver
- By adjusting the focal length, the beam angle can be changed from 15° to 90° or 15° to 70°
- Track head rotates through 355° and pivots through 90°

## **APPLICATION:**

- Optimum accent lighting for museums, exhibitions, art galleries, sales and showroom areas.















