

TECHNICAL DATA SHEET

LED Track Light, Adjustable Beam Angle / EN-TLI030-01, EN-TLI030-02

VERSION - 01.09.2017

STANDARD LUMINAIRE

Reference EN-TLI030-01 (Adjustable beam angle)

EN-TLI030-02 (Adjustable beam angle + buit-in dimmer)

Power 30 W 700 mA Current **Protection Class** IP20

Dimensions 3-pin track: ø75 x 176.5 x Ht.247.89mm

4-pin track: ø76 x 215.1 x Ht.258mm

Voltage AC220-240V, 50-60Hz Led Type Cree Cob Led

CRI 80+ OR 90+

Beam Angle Adjustable: 15° to 90° or 15° to 70°

Dimmable Yes

Installation Track, Pendant or Surface-Mounted

Working T° -20°C ~ +45°C Warranty 5 years

FINISH

Standard White, Black, Silver

ON REQUEST

CRI 80+, 90+

Beam Angle Adjustable: 15° to 90°

Adjustable: 15° to 70°

Installation Type On 3-pin track

On 4-pin track Pendant Surface-Mounted

Triac, 1-10V

Dimming Option Ask technical departement for more information

COLOR TEMPERATURE & LUMINOUS FLUX

EN-TLI030-01 + EN-TLI030-02

3'000K 4'000K 5'000K 2010 lm ±5% 2190 lm ±5% 2310 lm ±5% 2400 lm ±5%

CERTIFICAT

Œ

MAIN FEATURES:

- Sleek design with buit-in driver
- By adjusting the focal length, the beam angle can be changed from 15° to 90° or 15° to 70°
- Track head rotates through 355° and pivots through 90°

APPLICATION:

- Optimum accent lighting for museums, exhibitions, art galleries, sales and showroom areas.

















