

## TECHNICAL DATA SHEET

### TLFAL IP20 / Flex Led


VERSION - 30.04.2018

#### STANDARD LUMINAIRE


Reference	TLFAL
Protection Class	IP20
Lighting Source	Flex Led
Dimensions	26 x 21mm
Standard Length	330 - 670 - 1000 - 1330 - 1670 - 2000mm
Length on measure	on request up to 3000mm
Nb Lighting Unit	120 LED/m
Voltage	24V
Power	9.6W/m
Connecting Cable	1m standard cable 2x1.5mm <sup>2</sup>

#### APPLICATION: cornices, handrails, stairs, shelves

##### TLFAL / Flex Led



##### ON REQUEST: TLFAL Fixation TFCEP-S



##### ON REQUEST : Connecting plug AF/AMS



#### FINISH

##### Color Finishing Profil

Standard	Natural Anodised Aluminium
On request	Thermo-Enameling Powder Coating RAL Color Anodising Polished Aluminium Chrome Aspect Polished Aluminium Gold Aspect

#### ON REQUEST

Fixation	TFCP (Width: +3mm / Ht: +0.2mm) TFCP-S (Width: +3mm / Ht: +4.5mm)
Connecting Plug	AMS / AF
Dimming Option	1-10V, Dali, KNX <i>Ask technical departement for more information</i>

#### LIGHTING SOURCE

Lighting Source	Flex Led
Voltage	24V
Power	4.8W/m
Nb Led	60 LED/m - LED Pitch: 16.8mm
Beam Angle	120°
CRI	>80
Cut-Out	every 100mm
Lifetime	50'000h or 5 years
Working T°	-30°C to +75°C

#### Color Temperature & Luminous Flux / Meter

CCT	2700K	3000K	4000K
lm/m	390 lm	390 lm	425 lm

#### CERTIFICAT



#### AGABEKOV



AGABEKOV SA Manufacture 6, ROUTE DE COMPOIS  
CH-1222 VÉSENAZ - GENEVA - SWITZERLAND  
Tel. +41 22 752 47 45 Fax. +41 22 752 37 08  
E - mail: info@agabekov.com



AGABEKOV SA Bureau d'etudes 6, ROUTE DE COMPOIS  
CH-1222 VÉSENAZ - GENEVA - SWITZERLAND  
Tel. +41 22 752 47 45 Fax. +41 22 752 37 08  
Internet: www.agabekov.com

