

TECHNICAL DATA SHEET

TLFAL RGB IP20 / Aga-Led® Generation 2

VERSION - 10.11.2016


STANDARD LUMINAIRE

Reference	TLFAL RGB
Protection Class	IP20
Lighting Source	Aga-Led® RGB Generation 2
Connector	Festoon on B'Light conductor 16mm ²
Dimension	26 x 14mm
Standard Length	330 - 670 - 1000 - 1330 - 1670 - 2000mm
Length on measure	on request up to 3000mm
Nb Lighting Unit	18 LED/m
Voltage	24V
Power	43.2W/m
Connecting Cable	1m standard cable 4x0.75mm ²

APPLICATION: cornices, handrails, stairs, shelves



TLFAL RGB / AGA-LED® TYPE RGB - Festoon




FINISH

Color Finishing Profil

Standard	Natural Anodised Aluminium
On request	Thermo-Enameling Powder Coating RAL Color Anodising Polished Aluminium Chrome Aspect Polished Aluminium Gold Aspect

ON REQUEST: TLFAL Fixation TFCEP-S



ON REQUEST

Fixation	TFCEP (Width: +3mm / Ht: +0.2mm) TFCEP-S (Width: +3mm / Ht: +4.5mm)
Connecting Plug	AMS / AF
Dimming Option	Dali, KNX <i>Ask technical departement for more information</i>

ON REQUEST : Connecting plug AF/AMS



LIGHTING SOURCE

Lighting Source	Aga-Led® Type RGB
Ref	09LS05B G2
Voltage	24V
Current	Red: 20mA-Green: 40mA-Blue: 40mA
Power	2.4W
Beam Angle	120°
Light Output - mcd	Red: 750 mcd Green: 2100 mcd Blue: 450 mcd
Lifetime	50'000h
Working T°	-20°C to +45°C
Environmental protection	Modified acrylate resin

CERTIFICAT



AGABEKOV



AGABEKOV SA Manufacture 6, ROUTE DE COMPOIS
CH-1222 VÉSENAZ - GENEVA - SWITZERLAND
Tel. +41 22 752 47 45 Fax. +41 22 752 37 08
E-mail: info@agabekov.com



AGABEKOV SA Bureau d'études 6, ROUTE DE COMPOIS
CH-1222 VÉSENAZ - GENEVA - SWITZERLAND
Tel. +41 22 752 47 45 Fax. +41 22 752 37 08
Internet: www.agabekov.com

